

BLANK PAGE



भारतीय मानक

हस्तचालित वर्गाकार ड्राइव साँकेट रिंचों के लिए चालन पुर्जे - विशिष्टि

भाग 2 आयाम

(पहला पुनरीक्षाण)

Indian Standard

DRIVING PARTS FOR HAND OPERATED SQUARE DRIVE SOCKET WRENCHES — SPECIFICATION

PART 2 DIMENSIONS

(First Revision)

UDC 621.883.16

© BIS 1991

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

FOREWORD

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by Assembly Hand Tools Sectional Committee had been approved by the Production Engineering Division Council.

This standard was first issued in 1976 based on ISO 3315: 1975. Consequent on its revision of ISO, this standard has been revised. The test torque values have been modified and aligned with revised ISO. Dimensions are in alignment with DIN 3122-1988.

This revised standard is in conformity with ISO 3315-1988 'Assembly tools for screws and nuts—Driving parts for hand operated square drive socket wrenches—Torque testing' issued by International Organization for Standardization (ISO). Assistance has also been derived from DIN 3122-1988 'Driving parts for hand operated squared drive socket wrenches' issued by Deutsches Institut für Normung (DIN).

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS 2:1960 'Rules for rounding off numerical values (revised)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

DRIVING PARTS FOR HAND OPERATED SQUARE DRIVE SOCKET WRENCHES — SPECIFICATION

PART 2 DIMENSIONS

(First Revision)

1 SCOPE

IS No.

Title

This standards covers dimensions for driving parts for hand operated square drive socket wrenches.

7214:1974

Specification for driving squares for hand socket

wrenches

2 REFERENCES

2.1 The following Indian Standards are necessary adjuncts to this standard:

IS No. 6293: 1981

Title

Nomenclature of the assembly tools for nuts and screws


(first revision)

3 NOMENCLATURE

3.1 Nomenclature of hand operated square drive socket wrenches shall be as given in IS 6293: 1981.

4 DIMENSIONS

4.1 Tee Handle, Square Drive




All dimensions in millimetres.

Nominal Dimension	a	d_1	d_2	1	Test Torque
of Driving Square	Max A	Max	Max	M a x	Min
					Nm
6.3	24	7	14	160	5 5
10	35	12	2 3	250	180
12.5	50	14	27	320	455
20	62	20	40	510	1 255
25	80	28	50	760	2 236

IS 7975 (Part 2): 1991


4.2 Speed Brace



All dimensions in millimetres.

Nominal Dimension	a	b	1	Test Torque
of Driving Square	Max	Max	Max	Min
				Nm
6.3	90	38	410	24
10	125	40	350	7 9
10	125	40	470	199
12.5	145	50	350	549
12.5	145	50	500	9 78

4.3 Ratchet Handle




All dimensions in millimetres

Nominal Dimension of Driving Square	a Ma x	b Max	c Max	l Max	Swing Angle ¹	Test Torque Min
6.3	12	25	25	150	26°	Nm 62
10	14	34	25	2 00	26°	202
12:5	21	50	38	275	26°	512
20	25	65	52	510	26°	1 412

¹Swing angle between two teeth.

4.4 Ratchet Handle, Reversible




All dimensions in millimetres.

Nominal Dimension of Driving Square	a Max	b Max	l Max	Swing Angle ¹	Test Torque Min
6.3	24	25	150	20°	Nm 62
10	36	35	200	20°	202
12.5	45	50	300	15°	512
20	60	70	630	15°	1 412
25	80	90	900	15°	2 515

¹Swing angle between two teeth.


4.5 Handle, Spin Type, Male Square



All dimensions in millimetres.

Nominal Dimension	l_1	l_2	Test Torque
of Driving Square	Max	Min	Min
			Nm
6.3	160	40	10
10	190	40	34


4.6 Nut Spinner, Flex Head



All dimensions in millimetres.

Nominal Dimension	1	Test Toque
of Driving Square	Max	Min
		Nm
6.3	160	62
10	260	202
12 ⁻ 5	250	512
12.5	400	512

4.7 Offset Handle, Square Drive



All dimensions in millimetres.

Nominal Dimension	l_1	l_2	Test Torque
of Driving Square	Max	Ma x	Min
			Nm
6.3	110	35	62
10	210	45	202
12.5	250	60	512

- **4.8** Driving square shall be in accordance with IS 7214: 1974 with a minimum hardness of 382 HV (\approx 39 HRC).
- 4.9 The illustrations given in 4.1 to 4.7 are diagrammatic only and are not intended to illustrate the details of design.

5 DESIGNATION

5.1 Tee Handle, Square Drive

A tee handle square drive with nominal dimension of driving square 12.5 mm length 320 mm shall be designated as:

Tee Handle IS 7975 (Part 2) -12.5×320

5.2 Speed Brace

A speed brace with nominal dimension of driving square 10 mm and length 470 mm shall be designated as:

Speed Brace IS 7975 (Part 2) -10×470

5.3 Ratchet Handle

A ratchet handle with nominal dimension of driving square 20 mm shall be designated as:

Ratchet Handle IS 7975 (Part 2)—20

5.4 Ratchet Handle Reversible

A ratchet handle reversible with nominal dimension of driving square 10 mm and length 200 mm shall be designated as:

Ratchet Handle Reversible IS 7975 (Part 2) -10 × 200

5.5 Handle, Spin Type, Male Square

A handle, spin type, male square with nominal dimension of driving square 6.3 mm shall be designated as:

Handle, Spin Type IS 7975 (Part 2) -6.3

5.6 Nut Spinner, Flex Head

A nut spinner, flex head with nominal dimension of driving square 12.5 mm shall be designated as:

Nut Spinner IS 7975 (Part 2) -12.5

5.7 Offset Handle, Square Drive

An offset handle, square drive with nominal dimension of driving square 10 mm shall be designated as:

Offset Handle IS 7975 (Part 2) -10

Standard Mark

The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

Bureau of Indian Standards

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publication), BIS.

Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc: No. PE 05 (5510)

NEW DELHI 110002

Western: Manakalaya, E9 MIDC, Marol, Andheri (East)

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected
	BUREAU OF INDIAN STANDARDS	
Headquarters:		
Manak Bhavan, 9 Bahadur Sh Telephones: 331 01 31, 331	nah Zafar Marg, New Delhi 110002 13 75	Telegrams: Manaksanstha (Common to all Offices)
Regional Offices:		Telephonc
Central: Manak Bhavan, 9 B	Bahadur Shah Zafar Marg	∫ 3 31 01 31

Eastern: 1/14 C.I.T. Scheme VII M, V.I.P. Road, Maniktola
CALCUTTA 700054

37.86.67

CALCUTTA 700054 37 86 62

Northern: SCO 445-446, Sector 35-C, CHANDIGARH 160036 53 38 43

Southern: C.I.T. Campus, IV Cross Road, MADRAS 600113 2350216

BOMBAY 400093

Branches: AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI.

HYDERABAD. JAIPUR. KANPUR. PATNA. THIRUVANANTHAPURAM.

331 13 75

6 32 92 95